This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



claure 1


Applied Pot.		Gas Velocities	cities				lon+Flow		Qvisc+Qaen	
^	<u>lo</u>	for Ls=Le	Ls	Re(Ls)	∆p(Ls)	Qohmic	Qvisc	Ogen	O total	Qideal
400	mol fraction	cm/s	cm/s	•	psid	Μm	ΜM	Wm	Αm	Wm
	1.000E-12	0.01	0.00	0.000	0.000010	0.0000000	1.238E-12	0.00001	1.11E-06	1.238E-12
lon Radius, rion	3.162E-12	0.04	0.00	0.000	0.000031	0.0000001	1.238E-11	0.000003	3.51E-06	1.238E-11
E	1.000E-11	0.12	0.00	0.00	0.000097	-	1.238E-10	0.000011	1.11E-05	1.238E-10
イ: 1:50E-08	3.162E-11	0.37	0.01	0.001	0.000307	0.0000005	1.238E-09	0.000035		1.238E-09
	1.000E-10	1.18	0.02	0.005	0.000971	0.0000017	•	0.000109		1.238E-08
Cap.Radius, rc	3.162E-10	3.72	0.07	0.005	0.003072	0.0000053		0.000346	က	1.238E-07
E C	1.000E-09	11.76	0.24	0.016	0.009715	0.0000168	1.238E-06	0.001095	•	1.238E-06
★。 0.005	3.162E-09	37.20	0.74	0.050	0.030721	0.030721 0.0000531	_	0.003465	.,,	1.238E-05
	1.000E-08	117.62		0.159	0.097147	0.0001684		0.010996	0.01	0.0001
Field Length, Le	3.162E-08	371.96	7.44	0.502	0.307206	0.0005383	0.00124	0.035152	0.04	0.0012
E)	1.000E-07	1176.23	23.52	1.586	0.971472	0.0017605		0.114973	0.13	0.0124
***	3.162E-07	3719.57		5.016	3.072064	,0.0061508	0.12379	0.401686	., 0.53	0.1238
	1.000E-06	11762.30	235.25	15.863	9.714720	0.0252860	XS	1.651345	X1291	X12379
Tot.Cap.Length, Ls	3.162E-06	37195.66	743.91	50.163	30.720642	0.720642 0.1383175	12.37871	9.033049		12.3787
Cm	1.000E-05	117623.02	2352.46	158.628	97.147201	1.0209592	123.78713	66.675372	191.48	123.7871
* 05 *	Drift Vel. in cm/s, vd =	n/s, vd =	461.747							
	NA, Avogadro Num. in 1/cm3 =	Num. in 1/cm	3=	2.883	2.8830E+19	}				
Eion, loniz.Energy	q, Electronic Charge in Cb =	Charge in Cb		1.602	.6022E-19	, ,				
•						Consideration of the Print Control of the Print Con				


Franke 2




7
13000
7

		1 "	Ž										
on Configurations	Ionization		_	1300	2400				1050		1300		
Electron Affinities and Electron Configurations		FIECTION	Configuration	$1s^1$	$1s^2$	$[He] 2s^1$	$[He] 2s^2$	$2s^2$	$2s^2$	$2s^2$	$2s^2$	[He] $2s^2 2p^5$	$2s^2$
Electron	Electron	Affinitv	(kJ/mol)	72.8	0>	59.8	0 >	27	122.3	0>	141.1	328.0	0>
		Element		н	Не	Li	Be	В	ŭ	Z	0	ĮŢ.	Ne







Flaure 7

Comparison of Performance Between Pumps Based on Different Technologies	erformance Be	etween Pu	mps Based o	n Differe	nt Technol	ogies		
Method	Base Unit Size x N	e x N	Frequency	Power	Power Voltage Flow Rate Ap	ow Rate	γV	
		mm3	Hz	mW	V	13/min	pisd	
Theoretical	•		DC	1.26	1.41	9.7		
Ion Drag	$10 \times 0.25 \times 1$	= 2.5	DC	1.65	401.41	9.7		4
MesoPump (elstatic, future)	5x5x0.5x15	= 188	25	14	100	1.0	10	
MesoPump (elstatic, today)	10x10x1x50	= 5000	3	25	150	1.0	10	
MesoPump (elstatic, today)	$10 \times 10 \times 1 \times 50$	= 5000	3	25	150	1.0	10	

ianre 9

86

7x7x1.1x7x14 = 5282

Piezo-Electric (Fraunhofer)

W 23

`	3						
ependence of tion	Ionizat.Energy E(+) in J/mol	1,000,000	exp(-E/RT)	3.169E-87	2.514E-35	1.123E-26	1.739E-21
Temperature Dependence of lon Concentration	<pre>lon Aff. Energy lonizat.Energy E(-) in J/mol E(+) in J/mol</pre>	100,000	exp(-E/RT)	2.239E-09	3.468E-04	2.541E-03	8.395E-03
	Temper. T in K			009	1500	2000	2500

Flaure 9

